

NLS-HR15 Series

NLS-HR1550-3E

Cordless 1D Bar Code Scanner

Support PDF417 & MircoPDF417



ZigBee

NLS-HR1550-3E 1D hand-held bar code scanner is the cordless model of HR15 series, which is also able to read PDF417 and MicroPDF417 stacked 2D bar code. This model adopts Zigbee technology to realize wireless communication and supports standard RS-232 / USB. With good performance, this rugged scanner is very suitable for applications in supermarkets, shopping malls and warehouse environment application, etc.

Product Features

- **Data Acquisition**
Support common 1D bar codes and PDF417 and MicroPDF417 stacked 2D bar code.
- **Operating Modes**
Data Transmission support Synchronous, Asynchronous and Batch mode. Offline Scanning up to 4095 EAN bar codes of 13mil.
- **Zigbee Wireless**
Zigbee technology, supporting long-distance communication up to 50m & easy networking to expand coverage
- **Super One Pair**
Cradle and scanner(s) can be paired one-to-one or one-to-many simply via the Match key on cradle. And the cradle is also able to seek the paired scanner(s) via the Match key.

Specifications

Performance	
Light Source	620nm Visible Red LED
Scan Pattern	CCD linear image
Symbologies	Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ISBN, Code 93, UCC/EAN-128, GS1 Databar, PDF417, MicroPDF417 etc. (Cordless model reading PDF417/MicroPDF417 data length is less than 255 bytes)
Resolution	≥ 4 mil
Scan Angle	42°
Reading Angle	42°
Scan Rate	300 scans per second
Minimum Symbol Contrast	20%
Reminder	Beep and LED indicator
Interface	RS-232, USB 1.1
Mechanical	
Dimensions of Scanner(L x W x H)	113.5 x 73 x 159 mm
Dimensions of Cradle(L x W x H)	195 x 82.5 x 47 mm
Weight of Cordless Scanner	210 g (Including battery)
Weight of Cradle	150 g
Reminder	Beep and LED indicator
Power Adaptor	Output: DC5V, ≥1.5A, Input: AC 100~240V, 50~60Hz
Environmental	
Operation Temperature	-10°C to 50°C (14°F to 122°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Humidity	5% ~ 95% (non-condensing)
Static Discharge	±12 kV (Air discharge), ±8 kV (Direct discharge)
Drop	1.5 m drop to concrete
Wireless	
Operating Modes	Synchronous, Asynchronous and Batch mode
Radio Technology	2.4 to 2.4835 GHz (ISM Band) frequency - Zigbee communication technology
Communication Range	≥ 50 m
Data Rate	20 KBps
Battery	2200 mAh Li-ion Battery
Expected Hours of Operation	17 hours
Charging Time	Around 4 hours for full charge
Number of Scan	60,000 scans per charge
Certificates	
FCC Part15 Class B, CE EMC Class B, CCC	

Contact Us

Newland China

+86-400-608-0591

sales@nlscan.cn

Newland Europe

+31(0)-345-87-0033

info@newland-id.com

Newland Taiwan

+886-2-7731-5388

info@newland-id.com.tw

Newland North America

+1-510-490-3888

info@newlandna.com

www.nlscan.com

Newland